

# & ACCESSORIES





....0.5%Rh 100°C

www.x-tremeseries.com

### **AUTO DRY CABINETS** XT-LINE CABINETS (1250 Liters)

## CABINET MODELS 9090

& ACCESSORIES = U = U 1200(w) X 1990(h) X 750(d)mm (		
MODEL	DESCRIPTION (STANDARD & OPTIONS)	
XT Line Dehumidifier Cabinets - 1250 Liters		
XTC-510-01  BASIC with 1  Dehumidifier Unit  Version 3.0	<ul> <li>1 ea Dehumidifier Unit</li> <li>Internal Humidity and Temperature Sensor</li> <li>7" Touch Screen Control Panel, 800*480 Pixel Screen Resolution</li> <li>Internet Connection by Wi-Fi or Ethernet Cable</li> <li>Remote Monitoring System (RMS)</li> <li>Datalogger (2GB)</li> <li>10 x Stainless Steel (SS) Shelves</li> <li>Door Alarm with Buzzer</li> <li>4 x Doors Double Insulated Glass</li> <li>Rear Stainless Steel (SS) Panels</li> <li>4 x Casters (2 of them are lockable)</li> <li>Adjustable Stabilization Legs 2 pcs</li> <li>Electrostatic Painted Metal Sheet Body - 1250 Liters Net</li> </ul>	
XTC-520-01 BASIC with 2 Dehumidifier Unit Version 3.0	<ul> <li>2 ea Dehumidifier Unit</li> <li>Internal Humidity and Temperature Sensor</li> <li>7" Touch Screen Control Panel, 800*480 Pixel Screen Resolution</li> <li>Internet Connection by Wi-Fi or Ethernet Cable</li> <li>Remote Monitoring System (RMS)</li> <li>Datalogger (2GB)</li> <li>10 x Stainless Steel (SS) Shelves</li> <li>Door Alarm with Buzzer</li> <li>4 x Doors Double Insulated Glass</li> <li>Rear Stainless Steel (SS) Panels</li> <li>4 x Casters (2 of them are lockable)</li> <li>Adjustable Stabilization Legs 2 pcs</li> <li>Electrostatic Painted Metal Sheet Body - 1250 Liters Net</li> </ul>	
XTC-510-S1 STANDARD CABINET 1 Version 3.0	<ul> <li>1 ea Dehumidifier Unit</li> <li>Indoor Light (XT-LGK-01)</li> <li>Internal Humidity and Temperature Sensor</li> <li>7" Touch Screen Control Panel, 800*480 Pixel Screen Resolution</li> <li>Internet Connection by Wi-Fi or Ethernet Cable</li> <li>Remote Monitoring System (RMS)</li> <li>Datalogger (2GB)</li> <li>10 x Stainless Steel (SS) Shelves</li> <li>Door Alarm with Buzzer</li> <li>4 x Doors Double Insulated Glass</li> <li>Rear Stainless Steel (SS) Panels</li> <li>4 x Casters (2 of them are lockable)</li> <li>Adjustable Stabilization Legs 2 pcs</li> <li>Electrostatic Painted Metal Sheet Body - 1250 Liters Net</li> </ul>	
	<ul> <li>1 ea Dehumidifier Unit</li> <li>Indoor Light (XT-LGK-01)</li> <li>Heater Kit (45 °C) Thermal Insulation and Only Stainless Steel (SS) BACK PANELS (XT-HTK-01)</li> <li>Internal Humidity and Temperature Sensor</li> <li>7" Touch Screen Control Panel, 800*480 Pixel Screen Resolution</li> <li>Internet Connection by Wisting or Ethernet Cable</li> </ul>	

#### XTC-510-S2

STANDARD CABINET 2 Version 3.0

- Internet Connection by Wi-Fi or Ethernet CableRemote Monitoring System (RMS)
- Datalogger (2GB)
- 10 x Stainless Steel (SS) Shelves
- Door Alarm with Buzzer
- 4 x Doors Double Insulated Glass
- Rear Stainless Steel (SS) Panels
- 4 x Casters (2 of them are lockable)
- Adjustable Stabilization Legs 2 pcs
  Electrostatic Painted Metal Sheet Body 1250 Liters Net

#### 1 ea Dehumidifier Unit Indoor Light (XT-LGK-01) Heater Kit (60 °C) and Double Wall Thermal Insulation and (SS) Panels ALL Sides (XT-HTK-02) Outside Humidity and Temperature Sensor (HTS-02) Internal Humidity and Temperature Sensor

#### XTC-510-S3

STANDARD CABINET 3 Version 3.0

- 7" Touch Screen Control Panel, 800\*480 Pixel Screen Resolution
- Internet Connection by Wi-Fi or Ethernet Cable
- Remote Monitoring System (RMS)
- Datalogger (2GB)
- 10 x Stainless Steel (SS) Shelves
- Door Alarm with Buzzer
- 4 x Doors Double Insulated Glass
- Rear Stainless Steel (SS) Panels
- 4 x Casters (2 of them are lockable)
- Adjustable Stabilization Legs 2 pcs
- Electrostatic Painted Metal Sheet Body 1250 Liters Net

XTC-510-S4 STANDARD CABINET 4 Version 3.0

- 1 ea Dehumidifier Unit
- Indoor Light (XT-LGK-01)
- Heater Kit (60 °C) and Double Wall Thermal Insulation and (SS) Panels ALL Sides (XT-HTK-02)
- Outside Humidity and Temperature Sensor (HTS-02)
- AUTO Door Locks (DLK-04)
- Internal Humidity and Temperature Sensor
- 7" Touch Screen Control Panel, 800\*480 Pixel Screen Resolution
- Internet Connection by Wi-Fi or Ethernet Cable
- Remote Monitoring System (RMS)
- Datalogger (2GB)
- 10 x Stainless Steel (SS) Shelves
- Door Alarm with Buzzer
- 4 x Doors Double Insulated Glass
- Rear Stainless Steel (SS) Panels
- 4 x Casters (2 of them are lockable)
- Adjustable Stabilization Legs 2 pcs
- Electrostatic Painted Metal Sheet Body 1250 Liters Net

STANDARD

CABINET 5

Version 3.0

- 2 ea Dehumidifier Unit
- Indoor Light (XT-LGK-01)
- Internal Humidity and Temperature Sensor
- 7" Touch Screen Control Panel, 800\*480 Pixel Screen Resolution
- Internet Connection by Wi-Fi or Ethernet Cable
- Remote Monitoring System (RMS) XTC-520-S5
  - Datalogger (2GB)
  - 10 x Stainless Steel (SS) Shelves
  - Door Alarm with Buzzer
  - 4 x Doors Double Insulated Glass
  - Rear Stainless Steel (SS) Panels
  - 4 x Casters (2 of them are lockable)
  - Adjustable Stabilization Legs 2 pcs
  - Electrostatic Painted Metal Sheet Body 1250 Liters Net

## • 2 ea Dehumidifier Unit

- Indoor Light (XT-LGK-01)
- Heater Kit (45 °C) Thermal Insulation and Only Stainless Steel (SS) BACK PANELS (XT-HTK-01)
- Internal Humidity and Temperature Sensor
- 7" Touch Screen Control Panel, 800\*480 Pixel Screen Resolution
- Internet Connection by Wi-Fi or Ethernet Cable
- Remote Monitoring System (RMS)
- Datalogger (2GB)
- 10 x Stainless Steel (SS) Shelves
- Door Alarm with Buzzer
- 4 x Doors Double Insulated Glass
- Rear Stainless Steel (SS) Panels
- 4 x Casters (2 of them are lockable)
- Adjustable Stabilization Legs 2 pcs
- Electrostatic Painted Metal Sheet Body 1250 Liters Net
- Version 3.0

XTC-520-S6

STANDARD

CABINET 6

## XTC-520-S7

Version 3.0

XTC-520-S8

STANDARD

CABINET

Version 3.0

- 2 ea Dehumidifier Unit
- Indoor Light (XT-LGK-01)
- Heater Kit (60 °C) and Double Wall Thermal Insulation and (SS) Panels ALL Sides (XT-HTK-02)
- Outside Humidity and Temperature Sensor (HTS-02)
- Internal Humidity and Temperature Sensor
- 7" Touch Screen Control Panel, 800\*480 Pixel Screen Resolution
- Internet Connection by Wi-Fi or Ethernet Cable
  Remote Monitoring System (RMS)
- STANDARD Hemote Monitoring
  CABINET 7 Datalogger (2GB)
  - 10 x Stainless Steel (SS) Shelves
  - Door Alarm with Buzzer
  - 4 x Doors Double Insulated Glass
  - Rear Stainless Steel (SS) Panels
  - 4 x Casters (2 of them are lockable)
  - Adjustable Stabilization Legs 2 pcs
  - Electrostatic Painted Metal Sheet Body 1250 Liters Net

#### • 2 ea Dehumidifier Unit

- Indoor Light (XT-LGK-01)
- Heater Kit (60 °C) and Double Wall Thermal Insulation and (SS) Panels ALL Sides (XT-HTK-02)
- Outside Humidity and Temperature Sensor (HTS-02)
- AUTO Door Locks (DLK-04)
- Internal Humidity and Temperature Sensor

#### • 7" Touch Screen Control Panel, 800\*480 Pixel Screen Resolution

- Internet Connection by Wi-Fi or Ethernet Cable
- Remote Monitoring System (RMS)
- Datalogger (2GB)
- 10 x Stainless Steel (SS) Shelves
- · Door Alarm with Buzzer
- 4 x Doors Double Insulated Glass
- Rear Stainless Steel (SS) Panels
- 4 x Casters (2 of them are lockable)
- Adjustable Stabilization Legs 2 pcs
- Electrostatic Painted Metal Sheet Body 1250 Liters Net

#### XT Line Smart Nitrogen (N2) Cabinets - With N2 Auto Flow System Only / 1250 Liters

#### XTC-N2

BASIC with N2 Auto Flow Unit Version 3.0

- 1 ea N2 Auto Flow Unit
- Internal Humidity and Temperature Sensor
- 7" Touch Screen Control Panel, 800\*480 Pixel Screen Resolution
- Internet Connection by Wi-Fi or Ethernet Cable
- Remote Monitoring System (RMS)
- Datalogger (2GB)
- 10 x Stainless Steel (SS) Shelves
- Door Alarm with Buzzer
- 4 x Doors Double Insulated Glass
- Rear Stainless Steel (SS) Panels
- 4 x Casters (2 of them are lockable)
- Adjustable Stabilization Legs 2 pcs
- Electrostatic Painted Metal Sheet Body 1250 Liters Net

#### XT Line Hybrid Cabinets - With N2 Auto Flow System + Dehumidifier Unit / 1250 Liters

### XTC-510-

BASIC with Dehumidifier and N2 Auto Flow Unit Version 3.0

- 1 ea Dehumidifier Unit
- 1 ea N2 Auto Flow Unit
- Internal Humidity and Temperature Sensor
- 7" Touch Screen Control Panel, 800\*480 Pixel Screen Resolution
- Internet Connection by Wi-Fi or Ethernet Cable
- Remote Monitoring System (RMS)
- Datalogger (2GB)
- 10 x Stainless Steel (SS) Shelves
- Door Alarm with Buzzer
- 4 x Doors Double Insulated Glass
- Rear Stainless Steel (SS) Panels
- 4 x Casters (2 of them are lockable)
- Adjustable Stabilization Legs 2 pcs
- Electrostatic Painted Metal Sheet Body 1250 Liters Net

XTC-520- DN2 BASIC with 2 Dehumidifier and N2 Auto Flow Unit Version 3.0	<ul> <li>2 ea Dehumidifier Unit</li> <li>1 ea N2 Auto Flow Unit</li> <li>Internal Humidity and Temperature Sensor</li> <li>7" Touch Screen Control Panel, 800*480 Pixel Screen Resolution</li> <li>Internet Connection by Wi-Fi or Ethernet Cable</li> <li>Remote Monitoring System (RMS)</li> <li>Datalogger (2GB)</li> <li>10 x Stainless Steel (SS) Shelves</li> <li>Door Alarm with Buzzer</li> <li>4 x Doors Double Insulated Glass</li> <li>Rear Stainless Steel (SS) Panels</li> <li>4 x Casters (2 of them are lockable)</li> <li>Adjustable Stabilization Legs 2 pcs</li> <li>Electrostatic Painted Metal Sheet Body - 1250 Liters Net</li> </ul>
--	--

#### **OPTIONS FOR XT LINE (Please add options to basic models to get desired configuration)**

ХТ-НТК-01	Heater Kit (45 °C) for XT Line, Thermal Insulation and Only Stainless Steel (SS) BACK PANELS - NO Stainless Steel (SS) Panels on the Left Side, Right Side, Bottom and Top
XT-HTK-02	Heater Kit (60 °C) for XT Line, Double Wall Thermal Insulation and Stainless Steel (SS) Panels ALL Sides (Left Side, Right Side, Bottom, Top, Back)
хт-нтк-оз	Heater Kit (100 °C) for XT Line, Reinforced Heating Unit and Fans. Full Double Wall Thermal Insulation and Stainless Steel (SS) Panels ALL Sides (Left Side, Right Side, Bottom, Top, Back)
XT-DR2-01	Two Door Option for XT Line
SSS-01	Stainless Steel (SS) Shelf for XT Line (2 each required for one level)
SD-01	Stainless Steel (SS) Sliding Shelf for XT Line (2 each required for one level)
DLK-04	Automatic Door Locks by Password for XT and XL Line
XT-LGK-01	Indoor Light for XT Line
XT-FS-01**	Custom Sliding Feeder Storage Solutions for XT Line

# CABINET MODELS 2020

#### **AUTO DRY CABINETS**

## XS-LINE CABINETS

XSC-300 (300 Liters) / XSC-600 (625 Liters) / XSC-900 (925 Liters)

## & ACCESSORIES 2020

606(w) X 1990(h) X 750(d)mm 606(w) X 1128(h) X 750(d)mm 4...

**DESCRIPTION** (STANDARD & OPTIONS)

#### XS Line Dehumidifier Cabinets-300 Liters XSC-300/ 625 Liters XSC-600/ 925 Liters XSC-900

- 1 ea Dehumidifier Unit
- Internal Humidity and Temperature Sensor
- 7" Touch Screen Control Panel, 800\*480 Pixel Screen Resolution
- Internet Connection by Wi-Fi or Ethernet Cable

XSC-300-01

**MODEL** 

BASIC with 1 Dehumidifier Unit Version 3.0

- Remote Monitoring System (RMS) Datalogger (2GB)
- 2 x Stainless Steel (SS) Shelves Door Alarm with Buzzer
- 1 Door Double Insulated Glass
- Rear Stainless Steel (SS) Panels
- 4 x Casters (2 of them are lockable)
- Adjustable Stabilization Legs 2 pcs
- Electrostatic Painted Metal Sheet Body 300 Liters Net

XSC-600-01 BASIC with 1 Dehumidifier Unit Version 3.0

- 1 ea Dehumidifier Unit
- Internal Humidity and Temperature Sensor
- 7" Touch Screen Control Panel, 800\*480 Pixel Screen Resolution
- Internet Connection by Wi-Fi or Ethernet Cable
- Remote Monitoring System (RMS)
- Datalogger (2GB)
- 5 x Stainless Steel (SS) Shelves
- Door Alarm with Buzzer
- 2 Doors Double Insulated Glass
- Rear Stainless Steel (SS) Panels
- 4 x Casters (2 of them are lockable)
- Adjustable Stabilization Legs 2 pcs
- Electrostatic Painted Metal Sheet Body 625 Liters Net

XSC-900-01 BASIC with 1 Dehumidifier Unit Version 3.0

- 1 ea Dehumidifier Unit
- Internal Humidity and Temperature Sensor
- 7" Touch Screen Control Panel, 800\*480 Pixel Screen Resolution
- Internet Connection by Wi-Fi or Ethernet Cable
- Remote Monitoring System (RMS)
- Datalogger (2GB)
- 5 x Stainless Steel (SS) Shelves
- Door Alarm with Buzzer
- 2 Doors Double Insulated Glass
- Rear Stainless Steel (SS) Panels
- 4 x Casters (2 of them are lockable)
- Adjustable Stabilization Legs 2 pcs
- Electrostatic Painted Metal Sheet Body 925 Liters Net

#### XS Line Smart Nitrogen (N2) Cabinets - With N2 Auto Flow System Only 300 Liters XSC- 300 / 625 Liters XSC-600 / 925 Liters XSC-900

- 1 ea N2 Auto Flow Unit
- Internal Humidity and Temperature Sensor
- 7" Touch Screen Control Panel, 800\*480 Pixel Screen Resolution
- Internet Connection by Wi-Fi or Ethernet Cable
- Remote Monitoring System (RMS)
- XSC-300-N2

BASIC with N2 Auto Flow Unit Version 3.0

- Datalogger (2GB)
- 2 x Stainless Steel (SS) Shelves
- Door Alarm with Buzzer
- 1 Door Double Insulated Glass
- Rear Stainless Steel (SS) Panels • 4 x Casters (2 of them are lockable)
- Adjustable Stabilization Legs 2 pcs
- Electrostatic Painted Metal Sheet Body 300 Liters Net

#### • 1 ea N2 Auto Flow Unit

- Internal Humidity and Temperature Sensor
- 7" Touch Screen Control Panel, 800\*480 Pixel Screen Resolution
- Internet Connection by Wi-Fi or Ethernet Cable
- Remote Monitoring System (RMS)
- Datalogger (2GB)
- 5 x Stainless Steel (SS) Shelves
- Door Alarm with Buzzer
- 2 Doors Double Insulated Glass
- Rear Stainless Steel (SS) Panels
- 4 x Casters (2 of them are lockable)
- Adjustable Stabilization Legs 2 pcs
- Electrostatic Painted Metal Sheet Body 625 Liters Net

#### XSC-900-N2

XSC-600-N2

BASIC with N2

Auto Flow Unit

Version 3.0

BASIC with N2 Auto Flow Unit Version 3.0

1 ea N2 Auto Flow Unit

- Internal Humidity and Temperature Sensor
- 7" Touch Screen Control Panel, 800\*480 Pixel Screen Resolution
- Internet Connection by Wi-Fi or Ethernet Cable
- Remote Monitoring System (RMS)
- Datalogger (2GB)
- 5 x Stainless Steel (SS) Shelves
- · Door Alarm with Buzzer
- 2 Doors Double Insulated Glass
- Rear Stainless Steel (SS) Panels
- 4 x Casters (2 of them are lockable)
- Adjustable Stabilization Legs 2 pcs
- Electrostatic Painted Metal Sheet Body 925 Liters Net

#### XS Line Hybrid Cabinets - With N2 Auto Flow System + Dehumidifier Unit 300 Liters XSC- 300 / 625 Liters XSC-600 / 925 Liters XSC-900

- 1 ea Dehumidifier Unit
- 1 ea N2 Auto Flow Unit
- Internal Humidity and Temperature Sensor
- 7" Touch Screen Control Panel, 800\*480 Pixel Screen Resolution • Internet Connection by Wi-Fi or Ethernet Cable

#### XSC-300-DN2

BASIC with 1 Dehumidifier and N2 Auto Flow Unit Version 3.0

- Remote Monitoring System (RMS) • Datalogger (2GB)
- 2 x Stainless Steel (SS) Shelves
- Door Alarm with Buzzer
- 1 Door Double Insulated Glass
- Rear Stainless Steel (SS) Panels
- 4 x Casters (2 of them are lockable)
- Adjustable Stabilization Legs 2 pcs
- Electrostatic Painted Metal Sheet Body 300 Liters Net

- 1 ea Dehumidifier Unit • 1 ea N2 Auto Flow Unit
- Internal Humidity and Temperature Sensor
- 7" Touch Screen Control Panel, 800\*480 Pixel Screen Resolution • Internet Connection by Wi-Fi or Ethernet Cable

#### XSC-600-DN2

BASIC with 1 Dehumidifier and N2 Auto Flow Unit. Version 3.0

- Remote Monitoring System (RMS)
- Datalogger (2GB) 5 x Stainless Steel (SS) Shelves
- Door Alarm with Buzzer
- 2 Doors Double Insulated Glass
- Rear Stainless Steel (SS) Panels
- 4 x Casters (2 of them are lockable)
- Adjustable Stabilization Legs 2 pcs
- Electrostatic Painted Metal Sheet Body 625 Liters Net

#### XSC-900-DN2 BASIC with 1

Dehumidifier and N2 Auto Flow Unit Version 3.0

- 1 ea Dehumidifier Unit
- 1 ea N2 Auto Flow Unit
- Internal Humidity and Temperature Sensor
- 7" Touch Screen Control Panel, 800\*480 Pixel Screen Resolution
- Internet Connection by Wi-Fi or Ethernet Cable
- Remote Monitoring System (RMS)
- Datalogger (2GB)
- 5 x Stainless Steel (SS) Shelves
- Door Alarm with Buzzer
- 2 Doors Double Insulated Glass
- Rear Stainless Steel (SS) Panels
- 4 x Casters (2 of them are lockable)
- Adjustable Stabilization Legs 2 pcs
- Electrostatic Painted Metal Sheet Body 925 Liters Net

#### **OPTIONS FOR XS LINE (Please add options to basic models to get desired configuration)**

XS-HTK-01	Heater Kit (45 °C) for XS Line, Thermal Insulation and Only Stainless Steel (SS) BACK PANELS - NO Stainless Steel (SS) Panels on the Left Side, Right Side, Bottom and Top
XS-HTK-02	Heater Kit (60 °C) for XSC-300, Double Wall Thermal Insulation and Stainless Steel (SS) Panels ALL Sides (Left Side, Right Side, Bottom, Top, Back)
хѕ-нтк-оз	Heater Kit (60 °C) for XSC-600, Double Wall Thermal Insulation and Stainless Steel (SS) Panels ALL Sides (Left Side, Right Side, Bottom, Top, Back)
XS-HTK-04	Heater Kit (60 °C) for XSC-900, Double Wall Thermal Insulation and Stainless Steel (SS) Panels ALL Sides (Left Side, Right Side, Bottom, Top, Back)
XS-HTK-05	Heater Kit (100 °C) for XSC-300, Reinforced Heating Unit and Fans. Full Double Wall Thermal Insulation and Stainless Steel (SS) Panels ALL Sides (Left Side, Right Side, Bottom, Top, Back)
XS-HTK-06	Heater Kit (100 °C) for XSC-600, Reinforced Heating Unit and Fans. Full Double Wall Thermal Insulation and Stainless Steel (SS) Panels ALL Sides (Left Side, Right Side, Bottom, Top, Back)
XS-HTK-07	Heater Kit (100 °C) for XSC-900, Reinforced Heating Unit and Fans. Full Double Wall Thermal Insulation and Stainless Steel (SS) Panels ALL Sides (Left Side, Right Side, Bottom, Top, Back)
SSS-01	Stainless Steel (SS) Shelf for XSC-300 and XSC-600
SSS-02	Stainless Steel (SS) Shelf for XSC-900
SD-01	Stainless Steel (SS) Sliding Shelf for XSC-300 and XSC-600
SD-02	Stainless Steel (SS) Sliding Shelf for XSC-900
DLK-01	Automatic Door Locks by Password for XSC-300
DLK-02	Automatic Door Locks by Password for XSC-600 and XSC-900
XS-LGK-01	Indoor Light for XSC-300
XS-LGK-02	Indoor Light for XSC-600 and XSC-900
XS-DOR-01	1 Door Option for XSC-600
XS-FS-01	Custom Sliding Feeder Storage Solutions for XS Line

# CABINET MODELS 2020

# AUTO DRY CABINETS XL-LINE CABINETS (1840 Liters)

## & ACCESSORIES 2020

1200(w) X 1990(h) X 1050(d)mm 4...

MODEL	DESCRIPTION (STANDARD & OPTIONS)		
	XL Line Dehumidifier Cabinets - 1840 Liters		
XLC-01 BASIC with 1 Dehumidifier Unit Version 3.0	<ul> <li>1 ea Dehumidifier Unit</li> <li>Internal Humidity and Temperature Sensor</li> <li>7" Touch Screen Control Panel, 800*480 Pixel Screen Resolution</li> <li>Internet Connection by Wi-Fi or Ethernet Cable</li> <li>Remote Monitoring System (RMS)</li> <li>Datalogger (2GB)</li> <li>No Shelves</li> <li>Door Alarm with Buzzer</li> <li>2 Doors Double Insulated Glass</li> <li>Rear Stainless Steel (SS) Panels</li> <li>6 x Casters (2 of them are lockable)</li> <li>Adjustable Stabilization Legs 2 pcs</li> <li>Electrostatic Painted Metal Sheet Body, Depth (93 cm Net) - 1840 liters Net</li> <li>Cabinet suitable for Long FEEDER Storage Solutions - Pls add options below</li> </ul>		
XLC-02 BASIC with 2 Dehumidifier Unit Version 3.0	<ul> <li>2 ea Dehumidifier Unit</li> <li>Internal Humidity and Temperature Sensor</li> <li>7" Touch Screen Control Panel, 800*480 Pixel Screen Resolution</li> <li>Internet Connection by Wi-Fi or Ethernet Cable</li> <li>Remote Monitoring System (RMS)</li> <li>Datalogger (2GB)</li> <li>No Shelves</li> <li>Door Alarm with Buzzer</li> <li>2 Doors Double Insulated Glass</li> <li>Rear Stainless (SS) Steel Panels</li> <li>6 x Casters (2 of them are lockable)</li> <li>Adjustable Stabilization Legs 2 pcs</li> <li>Electrostatic Painted Metal Sheet Body, Depth (93 cm Net) - 1840 liters Net</li> <li>Suitable for Long FEEDER Storage Solutions - Pls add options below</li> </ul>		
	XL Line Smart Nitrogen (N2) Cabinets - With N2 Auto Flow System Only 1840 Liters		

XLC-N2

BASIC with N2 Auto Flow Unit Version 3.0

- 1 each N2 Auto Flow Unit
- Internal Humidity and Temperature Sensor
- 7" Touch Screen Control Panel, 800\*480 Pixel Screen Resolution
- Internet Connection by Wi-Fi or Ethernet Cable
- Remote Monitoring System (RMS)
- N2 Datalogger (2GB)
  - No Shelves
  - Door Alarm with Buzzer
  - 2 Doors Double Insulated Glass
  - Rear Stainless (SS) Steel Panels
  - 6 x Casters (2 of them are lockable)
  - Adjustable Stabilization Legs 2 pcs
  - Electrostatic Painted Metal Sheet Body, Depth (93 cm Net) 1840 liters Net
  - Suitable for Long FEEDER Storage Solutions Pls add options below

<sup>\*\*\*</sup> Shelves are not included to the XL Line Cabinets in order to enable customized storage solutions.

#### 1840 Liters • 1 each Dehumidifier Unit • 1 each N2 Auto Flow Unit • Internal Humidity and Temperature Sensor • 7" Touch Screen Control Panel, 800\*480 Pixel Screen Resolution • Internet Connection by Wi-Fi or Ethernet Cable Remote Monitoring System (RMS) XLC-510-DN2 • Datalogger (2GB) BASIC with No Shelves Dehumidifier and N2 Auto Flow Unit • Door Alarm with Buzzer Version 3.0 • 2 Doors Double Insulated Glass • Rear Stainless Steel (SS) Panels • 6 x Casters (2 of them are lockable) Adjustable Stabilization Legs 2 pcs · Electrostatic Painted Metal Sheet Body, Depth (93 cm Net) - 1840 liters Net Suitable for Long FEEDER Storage Solutions - Pls add options below • 2 each Dehumidifier Unit • 1 each N2 Auto Flow Unit • Internal Humidity and Temperature Sensor • 7" Touch Screen Control Panel, 800\*480 Pixel Screen Resolution • Internet Connection by Wi-Fi or Ethernet Cable • Remote Monitoring System (RMS) XLC-520-DN2 • Datalogger (2GB) BASIC with 2 No Shelves Dehumidifier and N2 Auto Flow Unit Door Alarm with Buzzer Version 3.0 • 2 Doors Double Insulated Glass Rear Stainless Steel (SS) Panels • 6 x Casters (2 of them are lockable)

XL Line Hybrid Cabinets - With N2 Auto Flow System + Dehumidifier Unit

Adjustable Stabilization Legs 2 pcs

#### **OPTIONS FOR XL LINE (Please add options to basic models to get desired configuration)**

• Suitable for Long FEEDER Storage Solutions - Pls add options below

• Electrostatic Painted Metal Sheet Body, Depth (93 cm Net) - 1840 liters Net

XL-HTK-01	Heater Kit (45 °C) for XL Line, Thermal Insulation and Only Stainless Steel (SS) BACK PANELS - NO Stainless Steel (SS) Panels on the Left Side, Right Side, Bottom and Top
XL-HTK-02	Heater Kit (60 °C) for XL Line, Double Wall Thermal Insulation and Stainless Steel (SS) Panels ALL Sides (Left Side, Right Side, Bottom, Top, Back)
XL-HTK-03	Heater Kit (100 °C) for XL Line, Reinforced Heating Unit and Fans. Full Double Wall Thermal Insulation and Stainless Steel (SS) Panels ALL Sides (Left Side, Right Side, Bottom, Top, Back)
SSS-02	Stainless Steel (SS) Shelf for XL Line, x (2 required for one level)
SD-02	Stainless Steel (SS) Sliding Shelf for XL Line, x (2 required for one level)
XL-LGK-01	Indoor Light for XL Line
DLK-04	Automatic Door Locks by Password for XT and XL Line
XL-DR4-01	Four Door Option for XL Line
XL-FS-01**	Custom Sliding Feeder Storage Solution for XL Line

<sup>\*\*\*</sup> Shelves are not included to the XL Line Cabinets in order to enable customized storage solutions.

# OPTIONS & ACCESSORIES Options are valid for all cabinet models

RF-01	RFID Access
V3-01	Embedded Software Upgrade to Version 3.0 from Version 2.0
MSDTrack	MSD (Moisture Sensitive Device) Traceability Software
PCB-01	PCB Holder
XT-DSSU-03	Stainless Steel (SS) U Divider for XT Line XSC-300 and XSC-600
XT-DSSI-04	Stainless Steel (SS) I Divider for XT Line XSC-300 and XSC-600
XL-DSSU-03	Stainless Steel (SS) U Divider for XL Line and XSC-900
XL-DSSI-04	Stainless Steel (SS) I Divider for XL Line and XSC-900
SMDD-01	Stainless Steel (SS) SMD Reel Holder with 20 Divider Wire
LEG-01	Adjustable Stabilization Legs 2 pcs
XS-EXT-01	Extraction Unit for XSC-300 and XSC-600
XS-EXT-02	Extraction Unit for XSC-900
XT-EXT-01	Extraction Unit for XT Line
XL-EXT-01	Extraction Unit for XL Line
HTS-02	Outside Humidity and Temperature Sensor
EAL-01	External Alarm Bar with Magnetic Base, 2-Color Light and Buzzer
N2AF-01	N2 Auto Flow System
COAF-01	Cooling Unit
HUM-01	Humidifier Unit
HEPA-01	Hepa Filter Option-Class 1000 (ISO 6)
**	Please ask for a quote



